

Rectifier Diodes for Rotating Excitation

旋转励磁整流管

Feature

- Working under great centrifugal force

Application

- Generator or electromotor of rotating excitation

特点

- 可在较大离心力作用下工作

应用

- 同步发电机和电动机旋转励磁装置



Type	I _{F(AV)}		V _{RRM} V	I _{RRM} mA	I _{FSM} @T _{jm} &10ms kA	V _{FM} @25℃		α_n		R _{thjc} ℃/W	M ±10 % N.m	T _{jm} ℃	Outline
	A	@T _C				V	@I _{FM} A	Normal	Super speed				
		℃						g	g				
ZX16	16	85	800~1600	1	0.23	1.35	48	1250	2500	1.800	2	150	X1
ZX25	25	85	800~1600	1	0.3	1.35	75	1250	2500	1.200	2	150	
ZX40	40	85	800~1600	3	0.4	1.35	120	1250	2500	0.800	3.5	150	X2
ZX70	70	85	800~1600	5	1.0	1.35	210	1250	2500	0.450	3.5	150	
ZX100	100	85	800~1600	7	1.5	1.60	300	1250	2500	0.300	13	150	X3
ZX200	200	85	800~1600	14	3.0	1.60	600	1250	2500	0.200	16	150	X4 X5
ZX200	200	80	1800~3000	14	3.0	1.80		1250	2500	0.200	16	150	
ZX300	300	85	800~1600	21	4.5	1.60	900	5000	5500	0.110	16	150	X6 X7
ZX300	300	80	1800~3000	21	4.5	1.80		5000	5500	0.110	16	150	X8 X9 X15
ZX400	400	85	800~1600	30	6.0	1.60	1200	5000	5500	0.090	16	150	X10 X11
ZX400	400	80	1800~3000	30	6.0	1.80		5000	5500	0.090	16	150	X12
ZX500	500	85	800~1600	35	7.5	1.60	1500	5000	5500	0.068	16	150	X10
ZX500	500	80	1800~3000	35	7.5	1.80		5000	5500	0.068	16	150	
ZX800	800	85	800~1600	40	12.1	1.60		5000	5500	0.065	16	150	X13 X16
ZX800	800	80	1800~3000	40	12.1	1.80		5000	5500	0.065	16	150	
ZX860	860	85	1800~2700	60	13.0	1.40	1800	5000	7500	0.065	16	150	X14

